


# Model EGAXT3 Accelerometer



Miniature Triaxial Design  
DC Response, Critically Damped  
10,000g Over-range Stops  
Broad Temperature Range




The **Model EGAXT3** miniature triaxial accelerometer combines a damping ratio of 0.7 (Nominal) with built-in over-range stops that are set to protect the unit against 10,000g shocks. This is ideal for applications which may experience rough handling or in situations where the accelerometer must survive a high initial overload in order to make a low g measurement.

## FEATURES

- Miniature Triaxial, Low Weight
- Static and Dynamic Measurement
- Frequency Response through 3000 Hz
- ±1% Non-Linearity
- -40°C to +120°C Operating Range
- 10,000g Over-range Protection



## APPLICATIONS

- Flight Test & Control
- Launch Vehicles
- Robotics
- Shock Testing





## dimensions

### EGAXT3-F Dimensions



### EGAXT3 Dimensions



# Model EGAXT3 Accelerometer

## performance specifications

All values are typical at +24°C, 100Hz and 15Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice. Standard product parameters are described in PSC-1004 for Plug & Play DC Accelerometers.

Parameters										Notes
<b>DYNAMIC</b>										
Range (g)	±5	±10	±25	±50	±100	±250	±500	±1000	±2500	
Sensitivity (mV/g) <sup>1</sup>	5.2-11.3	4.2-9.0	2.1-4.5	1.57-3.38	1.05-2.25	.52-1.13	.35-.75	.17-.38	.07-.15	
Frequency Response min. (Hz)	0-120	0-140	0-300	0-350	0-400	0-500	0-750	0-1000	0-1400	±½ dB
Frequency Response nom. (Hz)	0-250	0-300	0-600	0-700	0-900	0-1000	0-1500	0-2000	0-3000	±½ dB
Natural Frequency (Hz)	500	600	1200	1400	1700	2000	3000	4000	6000	
Non-Linearity (%FSO)	±1	±1	±1	±1	±1	±1	±1	±1	±1	
Transverse Sensitivity (%)	<3	<3	<3	<3	<3	<3	<3	<3	<3	
Damping Ratio	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	Nominal
Shock Limit (g)	2000	2000	5000	5000	10000	10000	10000	10000	10000	
<b>ELECTRICAL</b>										
Zero Acceleration Output (mV)	±15									Differential
Excitation Voltage (Vdc)	15 (can be used from 2 to 15Vdc but lower excitation voltage will decrease sensitivity accordingly)									
Input Resistance (Ω)	2000									Nominal
Output Resistance (Ω)	1000									Nominal
Insulation Resistance (MΩ)	>100									@50Vdc
Ground Isolation	Isolated from Mounting Surface									
<b>ENVIRONMENTAL</b>										
Thermal Zero Shift	±2.5mV / 50°C (±2.5mV / 100°F)									
Thermal Sensitivity Shift	+1% to -4% / 50°C (+1% to -4% / 100°F)									
Operating Temperature	-40 to 120°C (-40 to 250°F)									
Compensated Temperature	20 to 80°C (70 to 170°F), contact factory for other temperature compensation options									
Storage Temperature	-40 to 120°C (-40 to 250°F)									
Humidity	Epoxy Sealed, IP61									
<b>PHYSICAL</b>										
Case Material	Stainless Steel									
Cable	4x #34 AWG PTFE Leads, 24 inch, each axis									
Weight	<6 grams									
Mounting	Adhesive or Screw Mount Versions Available (-F configuration)									
<sup>1</sup> Output is ratiometric to excitation voltage										
<b>Calibration supplied:</b>	CS-FREQ-0100	NIST Traceable Amplitude Calibration from 20Hz to ±1/2dB Frequency Response Limit								
<b>Optional accessories:</b>	101	Three Channel DC Signal Conditioner Amplifier								
	140	Auto-zero Inline Amplifier								

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

## ordering info

### EGAXT3-F-100-/Z1/L2M/C

| | | Options, otherwise leave blank  
 | | Range (100 is 100g)  
 | Housing, F for flange mount (otherwise leave blank)

### Compensated Temp Ranges:

Standard = +20 to +80°C (+70 to +170°F)  
 Z\* = Non standard, contact factory

### Excitation Voltage:

Standard = 15Vdc  
 V\* = Non standard, contact factory

### Special Cable Length:

L00F = Replace "00" with length in feet  
 L00M = Replace "00" with length in meter

### Connector Wired to Cable:

C = Microtech type male or equivalent

Example: EGAXT3-F-100-/L2M

Model EGAXT3, Flange Mount Housing, 100g Range, 2 Meter Cable Length