

# Model 633 Six-Degree of Freedom Sensor

schematic



Silicon MEMS 6DOF Sensor  
 $\pm 50$  to  $\pm 6000g$  Acceleration Range  
 $\pm 500$  to  $\pm 24,000^\circ/\text{sec}$  Rate Range  
 Miniature Compact Package  
 Rugged Shock Resistant Housing



The Model 633 6-DOF Sensor is an analog sensor that includes outputs of three gyroscope/rate sensors and three DC accelerometers in one small package. The rate sensors and accelerometers are aligned orthogonally to each other which allow the user to measure motions in all 6 degrees of freedom (6 DOF). Designed specifically for product research and development in harsh environments, the Model 633 can maintain its precision under high shock condition.



## FEATURES

- Low Noise Jacketed Cables
- Rugged Integral Strain Relief
- Reliable Silicon MEMS Sensors
- $-40$  to  $+105^\circ\text{C}$  Temperature Range
- Shock Resistant Package
- Low Cross-Axis Sensitivity
- SAE J211 Compliant Performance

## APPLICATIONS

- Auto Safety Crash Testing
- Dummy Instrumentation
- Pedestrian Impact
- Rollover Testing
- Motorsports
- Biomechanics Testing
- Shock & Impact Testing

## dimensions



# Model 633 Six-Degree of Freedom Sensor

## performance specifications

All values are typical at +24°C and 10Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice.

### Parameters

#### DYNAMIC (RATE SENSORS)

	±500	±1500	±6000	±12K	±18K	±24K	Notes
Range (deg/sec)	±500	±1500	±6000	±12K	±18K	±24K	
Sensitivity (mV/deg/sec)	4.00	1.33	0.333	0.167	0.111	0.083	Not ratiometric
Frequency Response (Hz)	0-1000	0-1000	0-1000	0-2000	0-2000	0-2000	+1dB/-3dB
Non-Linearity (%FSO)	±0.5	±0.5	±0.5	±0.5	±0.5	±0.5	BFSL
Cross-Axis Sensitivity (%)	<1	<1	<1	<1	<1	<1	
Shock Limit (g)	3000	3000	3000	5000	5000	5000	
Residual Noise (mV RMS)	3.66	1.20	3.30	1.22	1.50	1.20	Passband

#### DYNAMIC (ACCELERATION SENSORS)

	±50	±100	±200	±500	±2000	±6000	Notes
Range (g)	±50	±100	±200	±500	±2000	±6000	
Sensitivity (mV/g)	2.0	1.1	0.8	0.4	0.15	0.10	Ratiometric <sup>1</sup>
Frequency Response (Hz)	0-1000	0-1200	0-1500	0-2000	0-3500	0-3500	±1/2dB
Natural Frequency (Hz)	4000	6000	8000	10000	23000	26000	
Non-Linearity (%FSO)	±1.0	±1.0	±1.0	±1.0	±1.0	±1.0	
Transverse Sensitivity (%)	<3	<3	<3	<3	<3	<3	
Shock Limit (g)	5000	5000	5000	5000	10000	10000	
Damping Ratio	0.5	0.5	0.5	0.3	0.05	0.05	Typical

#### ELECTRICAL

Zero Acceleration Output (mV), Rate Sensors	±100						Differential
Zero Acceleration Output (mV), Accel Sensors	±25						
Excitation Voltage (Vdc), Rate Sensors	5 to 16						
Excitation Voltage (Vdc), Accel Sensors	2 to 10						
Excitation Current (mA), Rate Sensors	<8						
Influence of Linear Acceleration (deg/sec/g)	0.1						
Common Mode Voltage (Vdc), Rate Sensors	2.5						±5%
Full Scale Output Voltage (Vpk), Rate Sensors	±2						±15%
Output Resistance (Ω), Rate Sensors	400						
Input Resistance (Ω), Accel Sensors	2400 to 6000						
Output Resistance (Ω), Accel Sensors	2400 to 6000						
Insulation Resistance (MΩ)	>100						@100Vdc
Turn On Time (msec), Rate Sensors	<100						
Ground Isolation	Isolated from Mounting Surface						

#### ENVIRONMENTAL

Thermal Zero Shift, Rate Sensors (%FSO)	±2.5						-40 to +105°C
Thermal Sensitivity Shift, Rate Sensors (%)	±2.0						-40 to +105°C
Thermal Zero Shift, Accel Sensors (mV/°C)	-0.11 ±0.11						-40 to +105°C
Thermal Sensitivity Shift, Accel Sensors (%/°C)	-0.25 ±0.25						-40 to +105°C
Operating Temperature (°C)	-40 to +105						
Humidity (Active Element & Electronics)	Hermetically Solder Seal						
Humidity (Housing)	Epoxy Sealed, IP65						

#### PHYSICAL


Case Material	Stainless Steel						
Cable	2x Cables; 12x #30AWG Cond PFA Insulated, Braided Shield, PU Jacket						
Weight (cable not included)	35 grams						
Mounting	2x #2.56 or M2 Mounting Screw						
Mounting Torque	4 lb-in (0.45 N-m)						

<sup>1</sup> Output is ratiometric to excitation voltage

<b>Calibration supplied:</b>	CS-ARLIN CS-FREQ-0100	NIST Traceable Linearity Calibration to FS Range NIST Traceable Amplitude Calibration to FR Limit
<b>Supplied accessories:</b>	AC-D03548	2x #2-56 (3/4" length) Socket Head Cap Screw
<b>Optional accessories:</b>	121 140	3-Channel Precision Low Noise DC Amplifier Auto-zero Inline Amplifier

# Model 633 Six-Degree of Freedom Sensor

## schematic



The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

## ordering info

PART NUMBERING Model Number+Accel Range+Rate Range+Cable Length

633-GGG-RRR-ZZZ-XX

- | | | | \_\_\_\_\_ Special requirements, otherwise leave blank
- | | | | \_\_\_\_\_ Cable (120 is 120 inches)
- | | \_\_\_\_\_ Rate Range (-500 for 500deg/sec, -12K for 12000deg/sec)
- | \_\_\_\_\_ Accel Range (-050 for 50g, -2K for 2000g)

Example: 633-500-6K-120  
Model 633, 500g, 6000deg/sec, 120" Cable